



REV. 12/12/25 TC

## ALX PRO SYSTEM - SLOPE TECHNIQUE AND WP WRAP

DIVISION 07 18 13  
Pedestrian Traffic Coatings

SCALE : NTS



## KEYNOTES

- ① WP-40 Sheet Membrane
- ② WP-25 or WP-30 Lath
- ③ Base Coat
- ④ Westcoat Slope Technique
- ⑤ WP Wrap - WP-45 & WP-95
- ⑥ Fiberlath Resin Membrane
- ⑦ Slurry Coat
- ⑧ Texture Coat
- ⑨ SC-10 Topcoat
- ⑩ Drip Edge Metal (2"x4")  
26 gauge, bonderized
- ⑪ Wall-to-deck "L" Metal (6"x4")  
26 gauge, bonderized
- ⑫ Building Paper
- ⑬ Wall Finish

## IAPMO ER-587

- For maximum adhesion, WP-43 Sheet Membrane Primer should be used.
- Standard overlap is bottom to top with a 4" overlap.
- Apply WP-53 on all flashing seams and overlaps.
- Minimum 5/8" exterior grade plywood.
- Minimum 1/4" slope required on all decks
- Refer to local building codes and standards.
- Refer to all related Product and System Specification Sheets.

All details are for reference only and should be evaluated by architect. These details are not a substitute for specifications, plans or evaluation reports. Architect, consultant or similar professional should be review prior to major waterproofing applications.

**westcoat**  
SPECIALTY COATING SYSTEMS

4007 Lockridge Street • San Diego, CA • 92102  
800.250.4519 • [westcoat.com](http://westcoat.com)