



REV. 11/14/25 TC

KEYNOTES

- ① Exterior Grade Plywood
- ② WP-40 Sheet Membrane
- ③ Drip Edge Metal (2"x4")
26 gauge, bonderized
- ④ Wall-to-deck "L" Metal (6"x4")
26 gauge, bonderized
- ⑤ WP-25 Metal Lath or WP-30 Glass Lath
- ⑥ Base Coat
- ⑦ Slurry Coat
- ⑧ Texture Coat
- ⑨ SC-10 Topcoat
- ⑩ Continuous drip screed
- ⑪ Building Paper
- ⑫ Wall Finish

IAPMO ER -587

- For maximum adhesion, WP-43 Sheet Membrane Primer should be used.
- Standard overlap is bottom to top with a 4" overlap.
- Apply WP-53 on all flashing seams and overlaps.
- Minimum 5/8" exterior grade plywood.
- Minimum 1/4" slope required on all decks
- Refer to local building codes and standards.
- Refer to all related Product and System Specification Sheets.

All details are for reference only and should be evaluated by architect. These details are not a substitute for specifications, plans or evaluation reports. Architect, consultant or similar professional should be review prior to major waterproofing applications.

ALX SYSTEM - SYSTEM OVERVIEW

DIVISION 07 18 13
Pedestrian Traffic Coatings

SCALE : NTS



westcoat
4007 Lockridge Street • San Diego, CA • 92102
800.250.4519 • westcoat.com