



KEYNOTES

- ① Structural Design (by others)
- ② 5/8" MIN. Exterior Grade Plywood (3/4" Recommended)
- ③ Scupper (by others)
- ④ Slip Sheet
- ⑤ Skim Coat
- ⑥ Membrane with Fabric
- ⑦ Body Coat
- ⑧ Smoothing Coat
- ⑨ SC-10 Acrylic Topcoat
- ⑩ WP-53 Hybrid Sealant
- ⑪ Building Paper (by others)
- ⑫ Stucco Finish (by others)
- ⑬ Stucco Stop (by others)

IAPMO ER - 517

- Standard overlap is bottom to top with a 4" overlap.
- Apply WP-53 on all flashing seams and overlaps.
- Do not use copper flashing.
- Minimum 1/4" slope required on all decks
- Refer to local building codes and standards.
- Refer to system and product specification sheets.

All details are for reference only and should be evaluated by architect. These details are not a substitute for specifications, plans or evaluation reports. Architect, consultant or similar professional should review prior to major waterproofing applications.

MER-KO - SCUPPER DETAIL

DIVISION 07 18 13
Pedestrian Traffic Coatings

SCALE : NTS



westcoat
SPECIALTY COATING SYSTEMS

4007 Lockridge Street • San Diego, CA • 92102
800.250.4519 • westcoat.com