



KEYNOTES

- ① Drip Edge Metal (2"x4")
26 gauge, bonderized
- ② Wall-to-deck "L" Metal (6"x4")
26 gauge, bonderized
- ③ WP-53 Hybrid Sealant
- ④ Slip Sheet
- ⑤ Skim Coat
- ⑥ Membrane with Fabric (Flashing)
- ⑦ Membrane with Fabric (Deck)
- ⑧ Body Coat
- ⑨ Smoothing Coat
- ⑩ SC-10 Acrylic Topcoat
- ⑪ Continuous drip screed
- ⑫ Building Paper
- ⑬ Wall Finish

IAPMO ER - 517

- Standard overlap is bottom to top with a 4" overlap.
- Apply WP-53 on all flashing seams and overlaps.
- Do not use copper flashing.
- Minimum 1/4" slope required on all decks
- Refer to local building codes and standards.
- Refer to system and product specification sheets.

All details are for reference only and should be evaluated by architect. These details are not a substitute for specifications, plans or evaluation reports. Architect, consultant or similar professional should review prior to major waterproofing applications.

REV. 10/30/25 TC

MER-KO - SYSTEM OVERVIEW

DIVISION 07 18 13
Pedestrian Traffic Coatings

SCALE : NTS



westcoat
SPECIALTY COATING SYSTEMS

4007 Lockridge Street • San Diego, CA • 92102
800.250.4519 • westcoat.com