



CA

ACCESSORIES
ADDITIVES & ACCESSORIES

CA-04 Epoxy Thickener

Description

CA-04 Epoxy Thickener is an aggregate added to Westcoat epoxies to increase viscosity (thicken the material).

Advantages

- Easy to Mix
- Aids in holding aggregate

Uses

CA-04 is typically used when cove, vertical applications or crack filler are needed and can be used in EC-32, EC-34, EC-38 and EC-84 epoxies.

Packaging

2 and 5 gallon bucket

INSPECTION / PREPARATION

Inspection

Surface must be structurally sound, dry, and free of oil, grease, curing agents, dirt, dust or other foreign material that may prevent proper adhesion. Surface must be rough or porous.

Preparation

Surface must be properly prepared and primed as specified for system being installed, please read individual System Specification Sheet for details.

APPLICATION

Mixing

Mix part A&B of the epoxy together first, then add 1 to 5 quarts of CA-04 Epoxy Thickener per gallon of epoxy. Mix into epoxy with a mechanical mixer until completely combined and at the desired viscosity

Applying Product

Apply epoxy as stated in the particular System Specification Sheet.

Coverage

Coverage will vary depending on the thickness of the chosen epoxy product.

Dry Time

Adding CA-04 may shorten dry times of the epoxy.

LIMITATIONS

- This product is designed for professional use only.
- Be sure to measure and mix properly. Be aware of the pot life of mixed epoxy.
- Do not apply in temperatures below 50°F or above 90°F. Hot or cold weather may effect dry times.
- Not intended for use with any other epoxy brands.

- Will cause color variation in the epoxy product.
- May decrease flexibility of epoxy.
- Adding more of CA-04 may shorten the pot life.
- Do not use more CA-04 than recommended.

HEALTH PRECAUTIONS

During application wear protective eye wear and rubber gloves. If skin contact occurs wash thoroughly with soap and water. If eye contact occurs flush immediately with clean water for 15 minutes and contact a physician.

Warning

Keep out of reach of children. Not for internal consumption. For professional use only by a qualified technician.

DISCLAIMER

PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT

OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.

