

		westcoat® SPECIALTY COATING SYSTEMS	PRODUCT SPECIFICATION
CA	ACCESSORIES <small>ADDITIVES & ACCESSORIES</small>	CA-15 Cement Accelerator	

Description

CA-15 Cement Accelerator is a powder, that when added to Westcoat cements will reduce the dry time of the cements by 15-20% of the standard dry times.

Uses

CA-15 is designed for use with these Westcoat cements when a faster dry time is desired TC-1, TC-1W, TC-2, TC-3, TC-4, TC-5, TC-6 and TC-30. Typically used in cooler temperatures or when a faster turnaround is desired (Not designed for use with TC-25, TC-26, TC-27 or TC-29 cements).

Advantages

Accelerates Dry Time • Easy to Use • Blend on Site

Product Data			
Packaging	5 Gallon Pail	Colors	Gray & White
Coverages	N/A	Mix Ratio	1 quart per 50 lb bag of Westcoat cement
VOC Content	0 gm/l	Shelf Life	1 year in unopened packaging

Inspection

Surface must be prepared in the proper manner that is required in the System Specification sheet for the desired cement application.

Preparation

Refer to individual System Specification sheet prior to installation.

Mixing

Add up to 1 quart of CA-15 Cement Accelerator per 50 pound bag of Westcoat cement. Mix with a mechanical mixer until completely combined.

Coverage

Coverage will vary depending on the thickness of the chosen cement product.

Application

Apply cement as stated in the particular System Specification Sheet.

DISCLAIMER: PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.



westcoat[®]
SPECIALTY COATING SYSTEMS

**PRODUCT
SPECIFICATION**

CA

ACCESSORIES
ADDITIVES & ACCESSORIES

CA-15 Cement Accelerator

Dry Time

Dry times will decrease by 15-20% when 1 quart of CA-15 Cement Accelerator is added to a 50 pound bag of cement. Refer to System Specification Sheet for desired cement, for initial dry times.

Clean Up

Uncured material can be removed with an environmentally-safe solvent. If cured, material can only be removed mechanically.

Limitations

- This product is designed for professional use only.
- Not designed for use with TC-25, TC-26, TC-27 or TC-29 cements.
- Do not apply in temperatures below 55°F or above 95°F. Actual dry times will vary depending on humidity and volume of water added to mix.
- Not intended for use with any other cement brands.
- May cause color variation in the chosen cement product.
- It is strongly suggested that all limitations and attributes are disclosed to customer and end user.
- Do not use more CA-15 than recommended.
- Store material between 40°F and 90°F
- Do not allow any Westcoat products to freeze.

Health Precautions

Inhalation of vapor or mist can cause headache, nausea irritation of nose, throat, and lungs. Avoid breathing vapors, it is strongly recommended that respirators are worn. Prolonged or repeated skin contact can cause slight skin irritation. All epoxies have the potential of causing skin irritations or allergic reactions. Be careful not to get on skin, clothes or in eyes. Gloves are strongly recommended. If splashed in the eye, flush with warm water and contact a physician if blurring persists.

Solvent based products are extremely flammable, extinguish all pilot lights and sources of ignition such as electrical motors. Be sure to have adequate cross ventilation prior to installing.

Slip Precaution

Westcoat Specialty Coatings Systems highly recommends the use of a slip-resistant additive to all coatings/systems that may be exposed to wet, oily, greasy or slippery conditions. It is the end user's responsibility to provide a flooring system that meets current safety standards. Westcoat and its distributors will not be responsible for injury incurred during a slip and fall incident. For the current coefficient of friction requirements, please consult your local building codes.

DISCLAIMER: PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.



westcoat[®]

4007 Lockridge St • San Diego, CA 92102
800-250-4519 • Fax 619-255-7187 • westcoat.com

2 of 2
CA-15 12/19