



# SAFETY DATA SHEET

## Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Stamp Release

Product Code: 56-CA20-98

### WESTCOAT SPECIALTY COATING SYSTEMS

4007 Lockridge St  
San Diego, CA 92102

Information Telephone: 800-250-4519

Emergency Telephone: 800-424-9300

## Section 2 - HAZARDS IDENTIFICATION

### GHS Ratings:

Flammable liquid	4	Flash point $\geq 60^{\circ}\text{C}$ (140°F) and $\leq 93^{\circ}\text{C}$ (200°F)
Skin corrosive	2	Reversible adverse effects in dermal tissue, Draize score: $\geq 2.3 < 4.0$ or persistent inflammation
Eye corrosive	2A	Eye irritant: Subcategory 2A, Reversible in 21 days
Organ toxin single exposure	3	Transient target organ effects- Narcotic effects- Respiratory tract irritation
Aspiration hazard	1	Aspiration Toxicity Category 1: Known (regarded)- human evidence - hydrocarbons with kinematic viscosity $\geq 20.5 \text{ mm}^2/\text{s}$ at 40° C.

### GHS Hazards

H227	Combustible liquid
H304	May be fatal if swallowed and enters airways
H315	Causes skin irritation
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness or dizziness

### GHS Precautions

P210	Keep away from heat/sparks/open flames/hot surfaces – No smoking
P235	Keep cool
P261	Avoid breathing dust/fume/gas/mist/vapours/spray
P264	Wash ... thoroughly after handling
P271	Use only outdoors or in a well-ventilated area
P280	Wear protective gloves/protective clothing/eye protection/face protection
P312	Call a POISON CENTER or doctor/physician if you feel unwell
P321	Specific treatment (see ... on this label)
P331	Do NOT induce vomiting
P362	Take off contaminated clothing and wash before reuse
P301+P310	IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician
P302+P352	IF ON SKIN: Wash with soap and water
P304+P340	IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
P305+P351+P338	IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do – continue rinsing

P332+P313	If skin irritation occurs: Get medical advice/attention
P337+P313	If eye irritation persists, get medical advice/attention
P370+P378	In case of fire: Use ... for extinction
P405	Store locked up
P403+P233	Store in a well ventilated place. Keep container tightly closed
P403+P235	Store in a well ventilated place. Keep cool
P501	Dispose of contents/container to ...

**Signal Word: Danger**



### Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Petroleum distillates, hydrotreated light	64742-47-8	0.00% - 80.00%
Solvent naphtha, petroleum, heavy aliphatic	64742-96-7	0.00% - 80.00%

### Section 4 - FIRST AID MEASURES

#### **First aid measures for different exposure routes**

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

**EYE CONTACT:** Immediately flush eyes with plenty of water for a least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

**SKIN CONTACT:** Remove contaminated clothing. Wash skin with soap and water. Get medical attention if irritation develops or persists.

**INGESTION:** If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cups full of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively.

### Section 5 - FIRE-FIGHTING MEASURES

**EXTINGUISHING MEDIA:** Based on the NFPA guide, use dry chemical, alcohol foam, carbon dioxide, or other extinguishing agent suitable for class B fires. Use water to cool containers exposed to fire. For large fires, use water spray or fog, thoroughly drenching the burning material.

**SPECIAL FIREFIGHTING PROCEDURES:** Water maybe ineffective. Fire fighters should wear self-contained, NIOSH-approved breathing apparatus and full protective clothing. Fire or intense heat may cause violent rupture of packages. In the event of fire, cool tanks with water spray. Do not use a solid water stream as it may scatter and spread fire. After fire, flush area with water to prevent re-ignition. Do not allow run-off from firefighting to enter drains or watercourses.

UNUSUAL FIRE & EXPLOSION HAZARDS: Exposure to heat will produce irritating vapors. Insulate from heat, electrical equipment, sparks & open flame. Closed containers may explode when subject to high heat. Dense smoke & toxic fumes will result during combustion creating a health hazard.

## Section 6 - ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedures

STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED: Use protective equipment. Ensure adequate ventilation. Remove sources of ignition, cover with inert absorbent material and remove to disposal container. Obey all federal, state and local laws. This is a RCA hazardous waste per title 40 CFR 261, classified 12 D001.

WASTE DISPOSAL METHODS: Obey relevant federal, state and local laws. Do not contaminate any lakes streams, ponds or underground water supplies.

PRECAUTIONS: Avoid personal contact. Keep out of reach of children. Remove all sources of ignition. Ensure adequate ventilation.

## Section 7 - HANDLING AND STORAGE

PRECAUTION FOR SAFE HANDLING: (Always wear recommended personal equipment.) Ensure all equipment is electrical grounded before beginning transfer operations. Ensure adequate ventilation. Do not allow product to contact skin, eyes and clothing. Do not breathe vapors. Keep away from fire, sparks and heated surfaces. Keep container tightly closed in a dry and well-ventilated place.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: Use with adequate explosion proof ventilation, isolate from sources of heat, sparks or flames. Extinguish all sources of ignition, including remote pilot and lights. Maybe harmful if swallowed or inhaled.

## Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION

Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits
Petroleum distillates, hydrotreated light 64742-47-8	Not Established	Not Established	Not Established
Solvent naphtha, petroleum, heavy aliphatic 64742-96-7	Not Established	Not Established	Not Established

### Individual protection measures, such as personal protective equipment

RESPIRATION PROTECTION: If it is possible to generate significant levels of vapor or mists, a NIOSH approved or equivalent respirator is recommended.

VENTILATION: General ventilation is recommended. Additional local exhaust ventilation is recommended where vapors, mists or aerosols may be released.

PROTECTIVE GLOVES: Impermeable gloves to minimize skin contact.

EYE PROTECTION: Chemical splash goggles or full-face shield.

PROTECTIVE EQUIPMENT: Wear impervious gloves, apron & splash goggles where exposure is possible.

HYGIENE PRACTICES: Wash contaminated clothes before reuse.

PRECAUTIONS: Avoid personal contact; keep out of reach of children, wash hands before eating or smoking. Do not puncture, drop or slide containers closed.

### Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

<p><b>Appearance</b> : Liquid</p> <p><b>Odor threshold</b> : N/A</p> <p><b>Melting point</b> : N/A</p> <p><b>Flash Pt(F/C)</b> : 80-96°C / 176-205°F</p> <p><b>Flammability (solid, gas)</b> : Class III</p> <p><b>Vapor pressure</b> : 0.02-0.06 kPa @20°C (68°F)</p> <p><b>Relative density</b> : 0.774</p> <p><b>Partition coefficient:n- octanol/water</b> :</p> <p><b>Decomposition temp</b> : N/A</p>	<p><b>Odor</b> : Hydrocarbon-like</p> <p><b>PH</b> : N/A</p> <p><b>Boiling point</b> : 200-300°C / 392-572°F</p> <p><b>Evaporation rate</b> : Slower than ether</p> <p><b>LEL/UEL</b> : N/A</p> <p><b>Vapor density</b> : 4.5</p> <p><b>Solubility</b> : Negligible</p> <p><b>Autoignition temp</b> : 232-236°C</p> <p><b>Viscosity</b> : 0.1 mm<sup>2</sup>/s @ 40°C (104°F)</p>
---	---

### Section 10 - STABILITY AND REACTIVITY

STABILITY: STABLE.

CONDITIONS TO AVOID: High temperatures, open flame.

INCOMPATIBILITY: Keep away from oxidizing agents, strongly alkaline and strongly acid materials in order to avoid exothermic reactions.

HAZARDOUS POLYMERIZATION: Will not occur.

HAZARDOUS DECOMPOSITION PRODUCTS: Hazardous decomposition products include carbon monoxide and carbon dioxide (CO<sub>2</sub>).

### Section 11 - TOXICOLOGICAL INFORMATION

**Mixture Toxicity**  
**Component Toxicity**

Exposure to this material may affect the following organs:

### **EFFECTS OF OVEREXPOSURE**

#### **EYES:**

ACUTE - LIQUID, AEROSOLS OR VAPORS ARE SEVERELY IRRITATING AND CAN CAUSE PAIN, TEARING, REDDENING AND SWELLING. IF LEFT UNTREATED, CORNEAL DAMAGE CAN OCCUR AND INJURY IS SLOW TO HEAL, DAMAGE IS USUALLY REVERSIBLE.

CHRONIC - PROLONGED VAPOR CONTACT MAY CAUSE CONJUNCTIVITIS

#### **SKIN CONTACT:**

ACUTE - REPEATED OR PROLONGED SKIN CONTACT CAN RESULT IN DRY, DEFATTED AND CRACKED SKIN CAUSING INCREASED SUSCEPTIBILITY TO INFECTION. IN ADDITION IRRITATION MAY DEVELOP INTO DERMATITIS. SOLVENTS CAN PENETRATE THE SKIN AND MAY CAUSE EFFECTS SIMILAR TO THOSE IDENTIFIED UNDER ACUTE INHALATION SYMPTOMS.

CHRONIC - MAY CAUSE EFFECTS SIMILAR TO THOSE IDENTIFIED UNDER CHRONIC INHALATION EFFECTS.

#### **INHALATION:**

ACUTE - SOLVENT VAPORS ARE IRRITATING TO THE EYES NOSE AND THROAT. SYMPTOMS OF IRRITATION MAY INCLUDE RED, ITCHY EYES, DRYNESS OF THE THROAT AND A FEELING OF TIGHTNESS IN THE CHEST. OTHER POSSIBLE SYMPTOMS OF OVEREXPOSURE INCLUDE: HEADACHE, DIZZINESS, NAUSEA, NARCOSIS FATIGUE AND LOSS OF APPETITE.

CHRONIC - CHRONIC EXPOSURE TO ORGANIC SOLVENTS HAS BEEN ASSOCIATED WITH VARIOUS NEUROTOXIC EFFECTS INCLUDING PERMANENT BRAIN AND NERVOUS SYSTEM DAMAGE. SYMPTOMS INCLUDE LOSS OF MEMORY, LOSS OF INTELLECTUAL ABILITY AND LOSS OF COORDINATION.

#### **INGESTION:**

ACUTE - CAN RESULT IN IRRITATION OF THE DIGESTIVE TRACT. SYMPTOMS CAN INCLUDE SORE THROAT ABDOMINAL PAIN NAUSEA, VOMITING AND DIARRHEA. VOMITING MAY CAUSE ASPIRATION OF SOLVENT RESULTING IN CHEMICAL PNEUMONITIS.

CHRONIC - ND

CONDITIONS AGGRAVATED BY EXPOSURE: SKIN DISORDERS AND ALLERGIES.

### **Section 12 - ECOLOGICAL INFORMATION**

#### **Component Ecotoxicity**

Petroleum distillates, hydrotreated light	96 Hr LC50 Pimephales promelas: 45 mg/L [flow-through]; 96 Hr LC50 Lepomis macrochirus: 2.2 mg/L [static]; 96 Hr LC50 Oncorhynchus mykiss: 2.4 mg/L [static]
--	--

### **Section 13 - DISPOSAL CONSIDERATIONS**

WASTE DISPOSAL METHODS: Obey relevant federal, state and local laws. Do not contaminate any lakes streams, ponds or underground water supplies.

### **Section 14 - TRANSPORT INFORMATION**

This material is classified for transport as follows:

<b><u>Agency</u></b>	<b><u>Proper Shipping Name</u></b>	<b><u>UN Number</u></b>	<b><u>Packing Group</u></b>	<b><u>Hazard Class</u></b>
DOT	Paint Related Material	UN1263	III	3

**Section 15 - REGULATORY INFORMATION**

**State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):** WARNING!

This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

**CERCLA-SARA Hazard Category:** This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

- None

**Sara Section 313:** This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

- None

**Section 16 - OTHER INFORMATION**

**Hazardous Material Information System (HMIS)**

HEALTH	1	<b>HMIS &amp; NFPA Hazard Rating</b> Legend * = Chronic Health Hazard <b>0 = INSIGNIFICANT</b> <b>1 = SLIGHT</b> <b>2 = MODERATE</b> <b>3 = HIGH</b>
FLAMMABILITY	2	
PHYSICAL HAZARD	0	
PERSONAL PROTECTION	X	

Westcoat Specialty Coating Systems believes, to the best of its knowledge, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Westcoat Specialty Coating Systems makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

Date Prepared: 2/12/2021