

# **SAFETY DATA SHEET**

### **Section 1 - PRODUCT AND COMPANY IDENTIFICATION**

Product Name: Temper-Crete UV Topcoat Catalyst Product Code: CA-28-98

### **WESTCOAT SPECIALTY COATING SYSTEMS**

4007 Lockridge St San Diego, CA 92102 Information Telephone: 800-250-4519 Emergency Telephone: 800-424-9300

### Section 2 - HAZARDS IDENTIFICATION

### **GHS Ratings:**

exposure

Reproductive toxin 2
Organ toxin repeated 1

ı

Human or animal evidence possibly with other information Significant toxicity in humans- Reliable, good quality human case studies or epidemiological studies Presumed significant toxicity in humans- Animal studies with significant and/or severe toxic effects relevant to humans at generally low exposure (guidanc

# **GHS Hazards**

H361 Suspected of damaging fertility or the unborn child

H372 Causes damage to organs through prolonged or repeated exposure

H413 May cause long lasting harmful effects to aquatic life

### **GHS Precautions**

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P260 Do not breathe dust/fume/gas/mist/vapours/spray

P264 Wash ... thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P273 Avoid release to the environment

P281 Use personal protective equipment as required

P308+P313 IF exposed or concerned: Get medical advice/attention

P405 Store locked up

P403+P233 Store in a well ventilated place. Keep container tightly closed

P501 Dispose of contents/container to ...

Signal Word: Danger



Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS			
Chemical Name	CAS number	Weight Concentration %	
Stannane, bis(dodecylthio)dimethyl-	51287-84-4	75.00 - 100.00%	

#### **Section 4 - FIRST AID MEASURES**

# First aid measures for different exposure routes

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation.

EYE CONTACT: Immediately flush eyes with plenty of water for least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention if irritation develops or persists.

INGESTION: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cups full of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively.

### **Section 5 - FIRE-FIGHTING MEASURES**

EXTINGUISHING MEDIA: Regular Foam, Carbon Dioxide, Dry Chemical, and Water Spray.

UNUSUAL FIRE AND EXPLOSION HAZARDS: No unusual fire or explosion hazards noted. Keep containers tightly closed.

SPECIAL FIREFIGHTING PROCEDURES: Water may be used to cool closed containers to prevent buildup of steam. If water is used, fog nozzles are preferred.

# **Section 6 - ACCIDENTAL RELEASE MEASURES**

### Personal precautions, protective equipment and emergency procedures

FOR NON-EMERGENCY PERSONNEL: No action shall be taken involving any personal risk or without suitable training. Evacuate surrounding areas. Keep unnecessary and unprotected personnel from entering. Do not touch or walk through spilled material. Avoid breathing vapor or mist. Provide adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Put on appropriate personal protective equipment.

FOR EMERGENCY RESPONDERS: If specialized clothing is required to deal with the spillage, take note of any information in Section 8 on suitable and unsuitable materials. See also the information in "For non-emergency personnel".

### **Section 7 - HANDLING AND STORAGE**

PRECAUTION FOR SAFE HANDLING: Wash thoroughly after handling. Wash hands before eating. Remove contaminated clothing and launder before reuse. Use only with adequate ventilation. Follow all MSDS/label precautions even after container is emptied because it may retain product residues. Avoid breathing fumes, vapors, or mist. Avoid contact with eyes, skin and clothing.

CONDITIONS FOR SAFE STORAGE: Keep from freezing. Store in a dry, well ventilated place. Keep container tightly closed when not in use.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION				
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits	
Stannane, bis(dodecylthio) dimethyl- 51287-84-4	Not Established	Not Established	Not Established	

# Individual protection measures, such as personal protective equipment

ENGINEERING CONTROLS: Use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Prevent build-up of vapors by opening all doors and windows to achieve cross-ventilation.

RESPIRATORY PROTECTION: A respiratory protection program that meets OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.

SKIN PROTECTION: Use gloves to prevent prolonged skin contact. Nitrile or Neoprene gloves may afford adequate skin protection.

EYE PROTECTION: Use safety eyewear designed to protect against splash of liquids.

OTHER PROTECTIVE EQUIPMENT: Refer to safety supervisor or industrial hygienist for further information regarding personal protective equipment and its application. Refer to safety supervisor or industrial hygienist for further guidance regarding types of personal protective equipment and their applications.

HYGIENIC PRACTICES: Wash thoroughly with soap and water before eating, drinking or smoking. Remove contaminated clothing immediately and launder before reuse.

# **Section 9 - PHYSICAL AND CHEMICAL PROPERTIES**

Appearance : Liquid Odor : N/A
Odor threshold : N/A
PH : N/A

Melting point : N/A Boiling point : N/A

Flash Pt(F/C): 365°F / 185°C Evaporation rate: Slower than ether

Flammability (solid, gas): Non combustible liquid LEL/UEL: N/A

Vapor pressure : N/AVapor density : N/ARelative density : 1.03Solubility : None

Partition coefficient:n- N/A Autoignition temp : N/A octanol/water :

Decomposition temp: N/A Viscosity: N/A

#### Section 10 - STABILITY AND REACTIVITY

CONDITIONS TO AVOID: Avoid contact with strong acid and strong bases.

HAZARDOUS DECOMPOSITION: By open flame, carbon monoxide and carbon dioxide. When heated to decomposition, it emits acrid smoke and irritating fumes.

HAZARDOUS POLYMERIZATION: Will not occur under normal conditions.

STABILITY: This product is stable under normal storage conditions.

INCOMPATIBILITY: Incompatible with strong oxidizing agents, strong acids and strong alkalis.

### **Section 11 - TOXICOLOGICAL INFORMATION**

Mixture Toxicity
Component Toxicity

# **Effects of Overexposure**

EYE CONTACT: Causes eye irritation. Irritating, and may injure eye tissue if not removed promptly.

SKIN CONTACT: Substance may cause slight skin irritation. Low hazard for usual industrial handling or commercial handling by trained personnel.

INHALATION: Low hazard for usual industrial handling or commercial handling by trained personnel. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist.

INGESTION: Substance may be harmful if swallowed.

PRIMARY ROUTE(S) OF ENTRY: Eye Contact, Ingestion, Inhalation, Skin Absorption, Skin Contact.

# **Section 12 - ECOLOGICAL INFORMATION**

### **Component Ecotoxicity**

### **Section 13 - DISPOSAL CONSIDERATIONS**

DISPOSAL INFORMATION: Dispose of material in accordance to local, state, and federal regulations and ordinances . Do not allow to entering waterways, wastewater, soil, storm drains or sewer systems .

# **Section 14 - TRANSPORT INFORMATION**

This material is classified for transport as follows:

AgencyProper Shipping NameUN NumberPacking GroupHazard ClassDOTNon-Regulated Material

SDS for: Temper-Crete UV Topcoat Catalyst Page 4 of 5

### **Section 15 - REGULATORY INFORMATION**

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

**CERCLA-SARA Hazard Category**: This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

**Sara Section 313**: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

**EU Risk Phrases** 

**Safety Phrase** 

### **Section 16 - OTHER INFORMATION**

# **Hazardous Material Information System (HMIS)**



Westcoat Specialty Coating Systems believes, to the best of its knowledge, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Westcoat Specialty Coating Systems makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination. It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

Date Prepared: 6/14/2022