



CA

ACCESSORIES
ADDITIVES & ACCESSORIES

CA-35 Epoxy Accelerator

Description

CA-35 Epoxy Accelerator can be used in EC-12, EC-32, EC-34 and EC-50 to improve dry times.

Advantages

- Faster Cure
- Increases Hardness

Uses

CA-35 is used to speed up curing in Westcoat epoxies. It is typically used in cooler temperatures or when a faster turnaround is desired.

Packaging

4 ounce bottle

INSPECTION / PREPARATION

Inspection

Surface must be structurally sound, dry, and free of oil, grease, curing agents, dirt, dust or other foreign material that may prevent proper adhesion. Surface must be rough or porous.

Preparation

Surface must be properly prepared and primed as specified for system being installed, please read individual System Specification Sheet for details.

APPLICATION

Mixing

Add 1 to 4 ounces of CA-35 Epoxy Accelerator to 1 kit of epoxy after mixing part A&B together. Mix into epoxy with a mechanical mixer until completely combined.

Applying Product

Apply epoxy as stated in the particular System Specification Sheet.

Coverage

Coverage will vary depending on the thickness of the chosen epoxy product.

Dry Time

Dry times will increase by 15-25% when 4 ounces CA-35 Accelerator is used.

LIMITATIONS

- This product is designed for professional use only.
- Be sure to measure and mix properly. Be aware of the pot life of mixed epoxy.
- Do not apply in temperatures below 50°F or above 90°F. Hot or cold weather may effect dry times.
- Do not use if the temperature is above 70°F

- Not intended for use with any other epoxy brands.
- Will cause increased ambering in the epoxy product.
- Will reduce flexibility of epoxy.
- It is strongly suggested that all limitations and attributes are disclosed to customer and end user.
- Do not use more CA-35 than recommended.

HEALTH PRECAUTIONS

During application wear protective eye wear and rubber gloves. If skin contact occurs wash thoroughly with soap and water. If eye contact occurs flush immediately with clean water for 15 minutes and contact a physician.

Warning

Keep out of reach of children. Not for internal consumption. For professional use only by a qualified technician.

DISCLAIMER

PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT

OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.

