



**CA**

**ACCESSORIES**  
ADDITIVES & ACCESSORIES

## CA-97 Polyurethane Accelerator

### Description

CA-97 Polyurethane Accelerator can be used in EC-95 & EC-96 to decrease dry times.

### Advantages

- Faster Cure
- Increases Hardness

### Uses

CA-97 is used to speed up curing in Westcoat polyurethanes. It is typically used in cooler temperatures or when a faster turnaround is desired.

### Packaging

4 ounce bottle

## INSPECTION / PREPARATION

Surface must be prepared in the proper manner that is required in the System Specification sheet for the desired epoxy application.

Refer to individual System Specification sheet prior to installation.

## APPLICATION

### Mixing

Add 1 to 4 ounces of CA-97 Polyurethane Accelerator to 1 kit of polyurethane after mixing part A&B together. Mix into epoxy with a mechanical mixer until completely combined.

### Applying Product

Apply product as stated in the particular System Specification Sheet.

### Coverage

Coverage will vary depending on the thickness of the chosen polyurethane product.

### Dry Time

Dry times will increase by approximately 15-25% when 4 ounces CA-97 Accelerator is used. Temperature and humidity will also affect dry times.

## LIMITATIONS

- This product is designed for professional use only.
- Be sure to measure and mix properly.
- Do not apply in temperatures below 50°F or above 70°F. Hot or cold weather may effect dry times.
- Not intended for use with any other polyurethane brands.

- Pot life of the EC-95 and EC-96 will be shortened by 5-8 minutes
- It is strongly suggested that all limitations and attributes are disclosed to customer and end user.
- Do not use more CA-97 than recommended.

## HEALTH PRECAUTIONS

During application wear protective eye wear and rubber gloves. If skin contact occurs wash thoroughly with soap and water. If eye contact occurs flush immediately with clean water for 15 minutes and contact a physician.

### Warning

Keep out of reach of children. Not for internal consumption. For professional use only by a qualified technician.

## DISCLAIMER

PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT

OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.

