

SAFETY DATA SHEET

Section 1 - PRODUCT AND COMPANY IDENTIFICATION

Product Name: Canyon Product Code: 25-SC30-205

WESTCOAT SPECIALTY COATING SYSTEMS

Information Telephone: 800-250-4519 4007 Lockridge St Emergency Telephone: 800-424-9300 San Diego, CA 92102

Section 2 - HAZARDS IDENTIFICATION

GHS Ratings:

Acute Tox. 4 Oral>300+<=2000mg/kg **Oral Toxicity** Skin corrosive

Destruction of dermal tissue: Exposure < 3 min. Observation <

1 hour, visible necrosis in at least one animal

Eye corrosive 1 Serious eye damage: Irreversible damage 21 days after

exposure, Draize score: Corneal opacity >= 3, Iritis > 1.5

Respiratory sensitizer Respiratory sensitizer 1

Skin sensitizer 1 Skin sensitizer

GHS Hazards

H302 Harmful if swallowed

H314 Causes severe skin burns and eye damage H317 May cause an allergic skin reaction

May be harmful if inhaled H333

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled

H335 May cause respiratory irritation

H373 May cause damage to organs through prolonged or repeated exposure

GHS Precautions

P201 Obtain special instructions before use

P202 Do not handle until all safety precautions have been read and understood

P261 Avoid breathing dust/fume/gas/mist/vapours/spray

P262 Do not get in eyes, on skin, or on clothing P264 Wash ... thoroughly after handling

P270 Do not eat, drink or smoke when using this product

P272 Contaminated work clothing should not be allowed out of the workplace P280 Wear protective gloves/protective clothing/eye protection/face protection

P281 Use personal protective equipment as required

P310 Immediately call a POISON CENTER or doctor/physician

P330 Rinse mouth

P363 Wash contaminated clothing before reuse

P301+P312 IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell

P301+P330+P331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting

P302+P352 IF ON SKIN: Wash with soap and water

P303+P361+P353 IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse

skin with water/shower

SDS for: 25-SC30-205 Page 1 of 6 P304+P340 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for

breathing

P305+P351+P338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact

lenses if present and easy to do - continue rinsing

P308+P313 IF exposed or concerned: Get medical advice/attention
P333+P313 If skin irritation or a rash occurs: Get medical advice/attention

P405 Store locked up

Signal Word: Danger



Section 3 - COMPOSITION / INFORMATION ON INGREDIENTS

Chemical Name	CAS number	Weight Concentration %
Iron chloride (FeCl2)	7758-94-3	10.00% - 20.00%
Iron	7439-89-6	5.00% - 10.00%
Hydrochloric acid	7647-01-0	5.00% - 10.00%

Section 4 - FIRST AID MEASURES

First aid measures for different exposure routes

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get immediate medical attention. Do NOT use mouth-to-mouth resuscitation. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical assistance immediately.

EYE CONTACT: Immediately flush eyes with plenty of water for a least 15 minutes holding eyelids open. Get medical attention. Do NOT allow rubbing of eyes or keeping eyes closed.

SKIN CONTACT: Remove contaminated clothing. Wash skin with soap and water. Get medical attention if irritation develops or persists.

INGESTION: If swallowed, do not induce vomiting. If victim is conscious and alert, give 2 to 4 cups full of water or milk. Call a physician or poison control center immediately. Never give anything by mouth to an unconscious person. Treat symptomatically and supportively.

Aspiration hazard: Do not induce vomiting or give anything by mouth because this material can enter the lungs and cause severe lung damage. Get immediate medical attention.

Section 5 - FIRE-FIGHTING MEASURES

EXTINGUISHING MEDIA: Use dry chemical, Carbon dioxide, or regular foam.

FIREFIGHTING PROCEDURES: Move container away from fire area without risk. From a safe distance and keeping upwind, apply flooding amounts of water to sides of container exposed to fire for cooling purposes until well after the fire is extinguished.

SPECIAL FIREFIGHTING PROCEDURES: Use self-contained breathing apparatus. Extinguish using suitable agents

SDS for: 25-SC30-205 Page 2 of 6

for type of fire.

UNUSUAL FIRE HAZARDS: Hydrogen gas may form explosive mixtures in the air. At high temperature, toxic corrosive fumes of anhydrous gas may be emitted.

Section 6 - ACCIDENTAL RELEASE MEASURES

General: Clear all non-essential personnel from spill area. If indoors ventilate the area. Remove all sources of ignition. Provide cleanup personnel with proper protective equipment such as gloves, eyewear, protective clothing and breathing equipment as required.

Cleanup of Small Spills: Dike or impound material to prevent spreading and prevent further spillage if possible. Cover spill with appropriate absorbent material. Collect material in appropriate container or vessel. Remove containers to safe area and cover to await reclamation or disposal. Area may be rinsed with water but do not allow it to be flushed into sewers or natural waterways.

Cleanup of Large Spills: Contain material as above and contact local fire or police department for immediate emergency response.

Section 7 - HANDLING AND STORAGE

PRECAUTION FOR SAFE HANDLING: Dispose of empty container according to all regulations. Do not reuse this container. Avoid breathing vapor or mist. Do not get in eyes, on skin, or on clothing. Wash thoroughly after handling. When mixing, slowly add acid to water to minimize heat generation and spattering. Never add water to acid. Keep container tightly closed when not in use. Keep container properly labeled.

CONDITIONS FOR SAFE STORAGE, INCLUDING ANY INCOMPATIBILITIES: Keep container tightly closed when not in use. Store in a cool, dry place away from direct sunlight and heat to avoid container deterioration. Avoid storage at extreme high or low temperatures. Protect from freezing. Keep container properly labeled. Keep separated from incompatible substances. Store in acid-resistant plastic, glass containers, or rubber-lined steel containers. Do not store in aluminum containers or use aluminum fittings or transfer lines.

Section 8 - EXPOSURE CONTROLS / PERSONAL PROTECTION				
Chemical Name / CAS No.	OSHA Exposure Limits	ACGIH Exposure Limits	Other Exposure Limits	
Iron chloride (FeCl2) 7758-94-3	Not Established	Not Established	Not Established	
Iron 7439-89-6	Not Established	Not Established	Not Established	
Hydrochloric acid 7647-01-0	Not Established	2 ppm Ceiling	NIOSH: 5 ppm Ceiling; 7 mg/m3 Ceiling	

Individual protection measures, such as personal protective equipment

RESPIRATION PROTECTION: Use proper NIOSH-OSHA respirator for contamination levels found in work area.

VENTILATION: Use close system when possible. Provide local exhaust ventilation where vapor or mist may be

SDS for: 25-SC30-205 Page 3 of 6

generated. Ensure compliance with appliance exposure limits.

PROTECTIVE GLOVES: Wear impermeable glove. Glove contaminates with product should be discarded. Promptly remove clothing that becomes soiled with products.

EYE PROTECTION: Must wear splash-proof goggles or full-face shield to prevent exposure.

PROTECTIVE EQUIPMENT: Wear chemical resistant clothing and rubber boots when potential for contact with the material exists. Various application methods can dictate use of additional protective safety equipment, such as impermeable apron, etc., to minimize exposure. Before reuse, thoroughly clean any clothing or protective equipment that cannot be decontaminated, such as glove or shoes.

WORK / HYGIENE PRACTICES: Exercise stringent hygiene practices to minimize exposure. If contact occurs, wash any body part with soap and water immediately. Wash hands after use, and before eating, drinking or smoking.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Appearance : Liquid

Odor threshold: N/A

Melting point : N/A

Flash Pt(F/C): N/A

Flammability (solid, gas): Non combustible

Vapor pressure: N/A

Relative density: 1.27-1.33

Partition coefficient:n- N/A

octanol/water:

Decomposition temp: N/A

Odor: Acidic

PH: 2-3

Boiling point: N/A

Evaporation rate : <1 (Butyl Acetate=1)

LEL/UEL: N/A

Vapor density: N/A

Solubility: Soluble

Autoignition temp: N/A

Viscosity: N/A

Section 10 - STABILITY AND REACTIVITY

STABILITY: Stable under normal storage and handling conditions.

INCOMPATIBILITY: With strong oxidizing agents, strong caustics, alkalis and alkali metals, and common and active metal (which produce flammable hydrogen gas).

DECOMPOSITION OR BY PRODUCTS: In fire conditions products may include toxic and hazardous gases including fumes of hydrogen chloride, oxide of copper and chromium oxides.

HAZARDOUS POLYMERIZATION: Not reported to occur under normal temperatures and pressures.

Section 11 - TOXICOLOGICAL INFORMATION

Mixture Toxicity

Oral Toxicity LD50: 1,035mg/kg Inhalation Toxicity LC50: 17mg/L

Component Toxicity

7758-94-3 Iron chloride (FeCl2)

Oral LD50: 450 mg/kg (Rat)

SDS for: 25-SC30-205 Page 4 of 6

7439-89-6 Iron

Oral LD50: 984 mg/kg (Rat)

7647-01-0 Hydrochloric acid

Oral LD50: 238 - (Rat) Inhalation LC50: 2 mg/L (Rat)

Exposure to this material may affect the following organs:

Effects of Overexposure

EYE CONTACT: Severe eye irritation, conjunctivitis, corneal necrosis and burns with impairment or permanent eye damage.

SKIN CONTACT: Severe irritation, inflammation, ulceration, necrosis and chemical burns.

INGESTION: Burns of the mouth, throat, esophagus and stomach with consequent pain, uneasiness, nausea, salivation, vomiting, diarrhea, chills, shock and intense thirst.

INHALATION: Burning of the throat, coughing and choking.

Section 12 - ECOLOGICAL INFORMATION

Component Ecotoxitity

None

Section 13 - DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHODS: Follow all Federal, State and Local regulations when storing and disposing of substances. Do not allow material to run off work area, and final rinsing should be absorbed or vacuumed and disposed of in accordance with regulations. Consult local and federal guidelines for proper disposal of these materials.

OTHER PRECAUTIONS: Air Spill - knock down vapors with water spray, contain water as it may become corrosive and dispose of properly.

Section 14 - TRANSPORT INFORMATION

This material is classified for transport as follows:

Agency DOT Proper Shipping Name Corrosive liquids, n.o.s (Hydrochloric Acid) UN 1760 III

UN Number Packing Group Hazard Class

Section 15 - REGULATORY INFORMATION

State of California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): WARNING! This product contains the following chemicals which are listed by the State of California as carcinogenic or a reproductive toxin:

- None

CERCLA-SARA Hazard Category: This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

SDS for: 25-SC30-205 Page 5 of 6

7758-94-3 Iron chloride (FeCl2) 10 to 20 % 7647-01-0 Hydrochloric acid 5 to 10 %

Sara Section 313: This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

- None

Section 16 - OTHER INFORMATION

Hazardous Material Information System (HMIS)



Westcoat Specialty Coating Systems believes, to the best of its knowledge, the information contained herein to be accurate and reliable as of the date of this safety data sheet. However, because the conditions of handling, use, and storage of these materials are beyond our control, we assume no responsibility or liability for personal injury or property damage incurred by the use of these materials. Westcoat Specialty Coating Systems makes no warranty, expressed or implied, regarding the accuracy or reliability of the data or results obtained from their use. All materials may present unknown hazards and should be used with caution. The information and recommendations in this material safety data sheet are offered for the users' consideration and examination . It is the responsibility of the user to determine the final suitability of this information and to comply with all applicable international, federal, state, and local laws and regulations.

Date Prepared: 7/13/2020

SDS for: 25-SC30-205 Page 6 of 6