



**TC-40 LIQUID COLORANT**

**Description**

Westcoat TC-40 Liquid Colorant is a water-based slurry formulated with high pigment levels of 60-70%.

**Uses**

TC-40 is designed to tint Westcoat cement to a variety of colors. TC-40 may also be used with most other portland cement-based products, such as stucco or concrete.

**Advantages**

- Fade Resistant
- Mixes Easily
- Convenient Packaging
- Choice of Colors

Product Data				
<b>Packaging</b>	16 fl. oz.	<b>Color</b>	Bark Peach Straw Yellow	Cinnamon Clay Smoke Raw Umber
<b>Coverage</b>	Refer to System Specification			
<b>VOC Content</b>	0 gm/l	<b>Shelf Life</b>	1 year in unopened package	

**Inspection**

Please refer to the desired System Specification Sheet for further information regarding Inspection.

**Preparation**

Please refer to the desired System Specification Sheet for further information regarding Surface Preparation.

**Mixing**

After cement mix is blended with water and/or acrylic, carefully measure the desired amount of colorant using a small measuring cup or an oral syringe. The typical amount is 1-4 ounces per 50 pound bag of cement, not to exceed 10 ounces. Pour the colorant into the mix and blend with a mechanical mixer at 300-500 rpm. Make sure to rinse all the colorant from your measuring cup with water. You may also add the colorant to the water and/or acrylic before combining with the Westcoat cements or chosen stucco, concrete, or mortar mix.

**Applying Product**

Please refer to the desired System Specification Sheet for further information regarding Applying Product.

**Dry Time**

Please refer to the desired System Specification Sheet for further information regarding Dry Time.

**Clean Up**

Uncured material can be removed with soap and water.

DISCLAIMER: PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.



**westcoat**<sup>®</sup>  
SPECIALTY COATING SYSTEMS

**PRODUCT  
SPECIFICATION**

**TC**

**TEXTURE COAT**  
DECORATIVE TEXTURED SURFACES

## **TC-40 LIQUID COLORANT**

### **Limitations**

- This product is designed for professional use only.
- It is strongly recommended that a sample be approved by the customer before starting the application.
- Westcoat assumes no responsibility for color variations after placement of material.
- Read System Specification Sheets before beginning the project.
- Color will vary depending on application.
- Moisture will effect the color of uncured colored cements.
- Do not apply in temperatures below 50° or above 90°. Cooler temperatures will cause slower drying times
- Do not allow any Westcoat products to FREEZE.
- All materials should be kept between 50-75°F.

### **Health Precautions**

Inhalation of vapor or mist can cause headache, nausea irritation of nose, throat, and lungs. Avoid breathing vapors, it is strongly recommended that respirators are worn. Prolonged or repeated skin contact can cause slight skin irritation. Dry Pigments have the potential of causing skin irritations or allergic reactions. Be careful not to get on skin, clothes or in eyes. Gloves are strongly recommended. If splashed in the eye, flush with warm weather and contact a physician if blurring persists.

DISCLAIMER: PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.



**westcoat**<sup>®</sup>

4007 Lockridge St • San Diego, CA 92102  
800-250-4519 • Fax 619-255-7187 • westcoat.com

2 of 2  
TC-40 7/17