

TC-60 Color Chip

Description

Westcoat TC-60 Color Chip is an acrylic, broadcast medium that is available in 9 different color blends. It can be applied in decorative and industrial solutions.

Uses

TC-60 is used in the Liquid Granite™ and Liquid Terrazzo™ Systems and are designed for use in showrooms, restaurants, garages, recreation rooms, washrooms and kitchens. These systems are a decorative, durable, chemical resistant coating, which makes it perfect for residential and commercial applications. Liquid Granite™ and Liquid Terrazzo™ are designed to be used as a light duty coating.

Advantages

Long Lasting • Durable • Decorative • Variegated Finish • Choice of 9 Color Blends

Product Data			
Packaging	55 lb box	Color Blends	Atascadero, Dove Gray, Granite, Mocha Tweed, Niagra, Shadow, Sandstone, Storm Cloud, Desert Storm
Coverage	Refer to System Specification	Mix Ratio	N/A
VOC Content	0 gm/l	Shelf Life	Indefinite in unopened package

Inspection

Please refer to the desired System Specification Sheet for further information regarding Inspection.

Preparation

Please refer to the desired System Specification Sheet for further information regarding Surface Preparation.

Mixing

Please refer to the desired System Specification Sheet for detailed information regarding Mixing.


Applying Product

Please refer to the desired System Specification Sheet for further information regarding Application.

Dry Time

Please refer to the desired System Specification Sheet for further information regarding Dry Time.

DISCLAIMER: PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.



westcoat[®]
SPECIALTY COATING SYSTEMS

**PRODUCT
SPECIFICATION**

TC

TEXTURE COAT
DECORATIVE TEXTURED SURFACES

TC-60 Color Chip

Clean Up

Please refer to the desired System Specification Sheet for further information regarding Clean Up.

Limitations

- This product is designed for professional use only.
- It is strongly recommended that a sample be approved by the customer before starting the application.
- Westcoat assumes no responsibility for color variations after placement of material.
- Read System Specification Sheets before beginning the project.
- Color will vary depending on application.
- Do not allow any Westcoat products to freeze.

Health Precautions

Inhalation of vapor or mist can cause headache, nausea irritation of nose, throat and lungs. Avoid breathing vapors. It is strongly recommended that respirators are worn. Prolonged or repeated skin contact can cause slight skin irritation. Dry Pigments have the potential of causing skin irritations or allergic reactions. Be careful not to get on skin, clothes or in eyes. Gloves are strongly recommended. If splashed in the eye, flush with warm water and contact a physician if blurring persists.

DISCLAIMER: PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.



4007 Lockridge St • San Diego, CA 92102
800-250-4519 • Fax 619-255-7187 • westcoat.com

2 of 2
TC-60 12/22