



WP-25 Metal Lath

Description

Westcoat WP-25 Metal Lath is a high quality, G60 hot-dipped galvanized steel, expanded metal lath. It has a carefully formed diamond pattern to allow for proper embedment of Westcoat cements. WP-25 has a weight of 2.5 pounds per square yard and comes in 97 inch long by 27 inch wide sheets.

Uses

WP-25 Metal Lath is stapled to the plywood on Westcoat's ALX™, ALX™ Pro, ALX™ Interior, ALX™ Waterproofing Underlayment and ALX™/ALX™ Pro Solar Reflective Finish systems to provide reinforcement and allow the cements to bond to the plywood.

Advantages

Provides Reinforcement • Hot-Dipped Galvanized Steel • Made in the USA

Product Data			
Packaging	10 Sheets per bundle 25 Bundles (250 sheets) per pallet	Color	Galvanized Steel
Coverages	18.18 Square Feet per sheet	Mix Ratio	n/a
VOC Content	0 gm/l	Shelf Life	Indefinite when stored properly

Inspection

Please refer to the desired System Specification Sheet for information regarding Inspection.

Preparation

Please refer to the desired System Specification Sheet for information regarding Preparation. Surface should be prepared per industry standard.

Metal Lath Application

Place the WP-25 Metal Lath on the plywood and cut it to fit the area, making sure the edge of the lath is offset two inches from any parallel plywood seams. The lath should run across the grain of the plywood (across the long seams) when possible. The lath has a grain and it should be placed so that it curves down at the edge of the deck. The lath should be held back ½ inch from all deck edges. This will allow the coating material to be feathered with a brush. With the lath in place, start in the center working your way out, stapling the lath using 16-20 staples per square foot (minimum 1 inch crown x 5/8 inch long, 16-gauge non-corrosive Senco P10). Overlap the lath 1-2 inches and staple every 1-2 inches along the seam. With a hammer, pound down any seams or staples that are higher than the lath.

Please refer to the desired System Specification Sheet for information regarding further application.

DISCLAIMER: PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.





westcoat[®]
SPECIALTY COATING SYSTEMS

**PRODUCT
SPECIFICATION**

WP

WATERPROOF
RELIABLE MOISTURE BARRIERS

WP-25 Metal Lath

Clean Up

Pick up loose pieces and store or dispose of properly.

Maintenance

See System Specification Sheets for maintenance instructions on system being installed.

Health Precautions

Use of gloves and eye protection are strongly recommended.

Limitations

- Read System Specification Sheets for exact system you will be installing before beginning the project.
- For Professional Use Only

DISCLAIMER: PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.



4007 Lockridge St • San Diego, CA 92102
800-250-4519 • Fax 619-255-7187 • westcoat.com

2 of 2
WP-25 2/20