



WP

WATERPROOF
RELIABLE MOISTURE BARRIERS

WP-42 Sheet Membrane Mastic

Description

Westcoat WP-42 Sheet Membrane Mastic is used to terminate end laps and edges of the WP-40 Sheet Membrane.

Advantages

- Self-Sealing
- Waterproof
- Self-Adhering
- Economical
- User Friendly

Uses

WP-42 is used exclusively in conjunction with the WP-40 Sheet Membrane.

Packaging

WP-42 Sheet Membrane Mastic (10.5 ounce tubes)

INSPECTION / PREPARATION

Inspection

Be sure the surface is clean, dry and free of grease, paint, oil, dust or any foreign material that may prevent proper adhesion. All nails and screws must be flush with the surface. Concrete should be cured for a minimum of 28 days.

Preparation

Concrete should be scraped or ground to remove any protrusions. Any divots or holes should be pre-patched. On plywood be sure the surface is clean, dry and free of grease, paint, oil, dust or any foreign material that may prevent proper adhesion.

APPLICATION

Coverage

Approximately 25 linear feet per tube.

puncture inner seal. Apply with a caulking gun, smooth with a putty knife.

Applying Product

Surfaces should be clean, free of all debris, oils, and any foreign matter. Cut nozzle to desired bead size and

Clean Up

Clean excess sealant with acetone or similar solvent.

LIMITATIONS

- Do not apply to wet surfaces
- Store in cool dry conditions

- Shelf life is 1 year from manufacture date
- Do not allow any Westcoat products to freeze.

DISCLAIMER

PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT

OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.

