



westcoat[®]
SPECIALTY COATING SYSTEMS

**PRODUCT
SPECIFICATION**

WP

WATERPROOF
RELIABLE MOISTURE BARRIERS

WP-42 Sheet Membrane Mastic

Description

Westcoat WP-42 Sheet Membrane Mastic is used to terminate end laps and edges of the WP-40 Sheet Membrane.

Uses

WP-42 is used exclusively in conjunction with the WP-40 Sheet Membrane.

Advantages

Self-Sealing ▪ Waterproof ▪ Self-Adhering ▪ Economical ▪ User Friendly

Product Data			
Packaging	10.5 ounce tubes	Color	Black
Coverages	~25 linear feet / tube	Mix Ratio	n/a
VOC Content	104 gm/l	Shelf Life	1 year in unopened packaging

Inspection

Be sure the surface is clean, dry and free of grease, paint, oil, dust or any foreign material that may prevent proper adhesion. All nails and screws must be flush with the surface. Concrete should be cured for a minimum of 28 days.

Preparation

Concrete should be scraped or ground to remove any protrusions. Any divots or holes should be pre-patched. On plywood be sure the surface is clean, dry and free of grease, paint, oil, dust or any foreign material that may prevent proper adhesion.

Application

Surfaces should be clean, free of all debris, oils, and any foreign matter. Cut nozzle to desired bead size and puncture inner seal. Apply with a caulking gun, smooth with a putty knife.

Clean Up

Clean excess sealant with acetone or similar solvent.

Limitations

- Do not apply to wet surfaces.
- Store in cool, dry conditions.
- Do not allow any Westcoat products to freeze.

DISCLAIMER: PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.



westcoat[®]

4007 Lockridge St ▪ San Diego, CA 92102
800-250-4519 ▪ Fax 619-255-7187 ▪ westcoat.com

1 of 1
WP-42 10/17