



WP-45 Flashing Fabric

Description

Westcoat WP-45 Flashing Fabric is a high performance, non-woven polyester engineering fabric created using thermally bonded fibers of polyethylene terephthalate and polyethylene terephthalate/adipate.

Uses

WP-45 is used to reinforce the WP-95 Waterproofing Membrane in Westcoat’s WP Wrap System. WP-45 can also be used wherever a flex, reinforcing fabric is needed.

Advantages

Significantly Reduces Reflective Cracking • Flexible, Resists Tearing • High Tensile Strength • Easy to Install • Non-Adhesive • Tough and Durable

Product Data			
Packaging	300 LF Rolls (10" x 300')	Color	White
Coverages	~Varies depending on usage	Mix Ratio	n/a
VOC Content	0 gm/l	Shelf Life	Indefinite when properly stored in the original, unopened container

Inspection

Surface must be structurally sound, dry, and free of laitance, oil, grease, curing agents, dirt, dust or other foreign material that may prevent proper adhesion.

Preparation

Please refer to the desired System Specification Sheet for further information regarding Surface Preparation. Surface should be prepared per industry standard.

Application

Please refer to the desired System Specification Sheet for further information regarding Application. Typically, WP-45 should be applied over a wet, tack coat of WP-95, WP-90 or similar material and then placed with the fuzzy side down. Ensure that the WP-45 is firmly placed, with no air pockets or voids.

Storage & Handling

Store all materials off the ground, in a dry environment, at temperatures between 50°F and 90°F and not in direct sunlight. All materials should be stored in compliance with local fire and safety requirements. Always wear proper safety equipment, including particle mask, eye protection and gloves when mixing and/or applying these products.

DISCLAIMER: PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.



westcoat[®]
SPECIALTY COATING SYSTEMS

**PRODUCT
SPECIFICATION**

WP

WATERPROOF
RELIABLE MOISTURE BARRIERS

WP-45 Flashing Fabric

Health Precautions

Inhalation of vapor or mist can cause headache, nausea, irritation of nose, throat and lungs. Prolonged or repeated skin contact can cause slight skin irritation. Wear rubber gloves and eye protection. Avoid eye contact and prolonged contact with skin. Wash thoroughly after handling. If eye contact occurs, flush with water for 15 minutes. Call a physician immediately.

Limitations

- The substrate surface must be structurally sound, clean, dry and free of laitance, dirt, dust, oil, grease, paint or other contaminants at the time of material application.
- Substrate and ambient temperature must be above 55°F and below 90°F during and for 24 hours following the application.
- Do not apply in inclement weather or when rain is occurring or expected within 24 hours.
- For Professional Use Only
- Must be incorporated into the waterproof membrane during application.
- Not intended for use as a finished surface.
- Avoid exposing to sharp objects that could cut or puncture the material.

DISCLAIMER: PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.