



## KEYNOTES

- ① Concrete Substrate (by others)
- ② EC-72 Epoxy Patch Gel
- ③ 26 Gauge Bonderized Sheet Metal
- ④ WP-47H Fiberlath Heavy Duty
- ⑤ Base Coat
- ⑥ Slurry Coat
- ⑦ Optional Texture Coat
- ⑧ SC-10 Topcoat
- ⑨ Continuous drip screed (by others)
- ⑩ Building Paper (by others)
- ⑪ Wall Finish (by others)

## IAMPO ER-587

- Concrete must be a min 2" thick & 2,500 PSI.
- Concrete should be prepared to a profile equal to CSP 3.
- Standard overlap is bottom to top with a 4" overlap.
- Apply WP-53 on all flashing seams and overlaps.
- Minimum 1/4" slope required on all decks
- Refer to local building codes and standards.
- Refer to all related Product and System Specifications for additional information.

All details are for reference only and should be evaluated by architect. These details are not a substitute for specifications, plans or evaluation reports. Architect, consultant or similar professional should review prior to major waterproofing applications.

REV. 5/12/25 TC

## MACOAT SYSTEM - OVERVIEW

DIVISION 07 18 13  
Pedestrian Traffic Coatings

SCALE : NTS



**westcoat®**

4007 Lockridge Street • San Diego, CA • 92102  
800.250.4519 • westcoat.com