



## 11-10 Training

Welcome to Westcoat's Self-Educated Training. The purpose of this course is to increase your knowledge of the 11-10 system.

This is a two-step process that will take approximately 45 - 60 minutes to complete. You will be required to complete a short test and submit your answers.

### Education

1. Spec Sheet: These spec sheets contain detailed information on uses, materials and coverage rates for this system. The specs also have detailed instructions on the proper application steps from preparation to final coat to achieve a successful installation. Click below to read the spec sheets:

**11-10 Standard**

**11-10 Custom**

2. Materials Cost: Westcoat's Materials Cost Template is a powerful tool for you and your customers. Click below, find and download the Material Cost Template, then estimate the materials and associated cost a 500 sq ft job.

11-10 System Page > scroll down to find the **Material Cost Template**

\*Alternatively, the **Material Estimator** shows the material needed without pricing.

3. Color Chart: The 11-10 system is available in a variety of colors and finishes, click to review the color charts:

**Topcoats**

**Water-Based Stain**

4. Tools: Get familiar with the recommended tools needed to install this system.

**11-10 Tool Guide**

Now to test all the valuable knowledge you've learned, continue to the next page.

## TEST

1. The 11-10 system is composed of what two products?  
EC-11 Epoxy Primer and SC-10 Acrylic Topcoat  
SC-11 Epoxy Topcoat and EC-10 Acrylic Primer
2. What should you do if the concrete moisture emissions exceed 5 lbs/1000 sf?  
Proceed with application  
Contact manufacturer
3. What is 11-10 specially designed to do?  
Waterproof decks and balconies.  
To be used as a topcoat for Westcoat systems.
4. How should the concrete be profiled?  
To CSP 3  
Wash and sweep it.
5. 11-10 can be installed over previously coated acrylic deck coatings.  
True  
False
6. What is the coverage rate of the Primer coat in the standard system?  
100-200 square feet per gallon.  
500-800 square feet per gallon.
7. What is the coverage rate of the Topcoat in the standard system?  
200-400 square feet per gallon.  
50-100 square feet per gallon.
8. What can be added for additional skid resistance?  
Safe Grip  
Textured SC-10
9. How does 11-10 Custom differ from the Standard system?  
The addition of the water-based stain and a protective sealer.  
Adding Safe Grip
10. What is the coverage rate for the WB Stain in the custom system?  
200-400 square feet per gallon.  
400-600 square feet per gallon.

**Name:**

**Branch name/Location:**