

| | | | |
|---|--|---|----------------------------------|
|  | | westcoat® SPECIALTY COATING SYSTEMS | PRODUCT SPECIFICATION |
| CA | ACCESSORIES <small>ADDITIVES & ACCESSORIES</small> | CA-20 Stamp Release | |

Description

Westcoat's CA-20 Stamp Release is a colorless release agent, designed to keep stamping mats from sticking to Westcoat's TC-06 Stamp Texture Cement. CA-20 forms a lubricating barrier that prolongs the life of stamping mats by decreasing the friction between the stamping mat and the cement, which allows the stamp to be removed without damaging the cement texture.

Uses

CA-20 Stamp Release is used in the Stamp-It™ System to transform aesthetically unattractive concrete into a very decorative surface. For use over existing concrete substrates such as: driveways, walkways, patios, garage floors, courtyards, entryways, interior floors, restaurant floors, showrooms and pool decks in both commercial and residential environments.

Advantages

Easy to Use • Decreases Friction • Minimal Cleanup • Can be Used Indoors and Outdoors • Works for Both Colored and Uncolored Concrete

| Product Data | | | |
|--------------------|---------------|-------------------|-------------------------------|
| Packaging | 5 Gallon Pail | Colors | Clear |
| Coverages | ~200 ft²/gal | Mix Ratio | N/A |
| VOC Content | 0 gm/l | Shelf Life | 2 years in unopened packaging |

Inspection

Concrete must be clean, dry and free of grease, paint, oil, dust, curing agents, laitance or any foreign material that will prevent proper adhesion. Drainage problems or puddling must be corrected prior to the installation of Stamp-It™. The concrete should be at least 2,500 PSI, 3½ inches thick and meet local building codes.

Preparation

Refer to the Stamp-It™ System Specification sheet prior to installation for preparation instructions.

Mixing

Stir prior to using.

Coverage

Coverage will vary depending on the timing, finish and job conditions, but approximately 200 square feet per gallon.

DISCLAIMER: PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.



westcoat[®]
SPECIALTY COATING SYSTEMS

**PRODUCT
SPECIFICATION**

CA

ACCESSORIES
ADDITIVES & ACCESSORIES

CA-20 Stamp Release

Application

Allow the TC-06 Stamp Texture Cement to become firm enough for stamping. Your hand should be able to slightly indent the surface, but the surface should not be too soft. When it is firm enough, lightly spray the surface with CA-20 Stamp Release. Apply the release to the stamps as well. Place the stamps onto the surface and impress them slightly to create the necessary effect. To maintain the integrity of the TC-06, avoid mixing the CA-20 into the TC-06. Timing is everything. You should use caution if you are new to this process. Continue to mix, spread and stamp as you go, paying special attention to timing.

Dry Time

The product will dry at different rates depending on mixing, temperature, humidity and whether or not you are working in the shade or sun. At 55F degrees, stamping should be done in 3-5 hours, at 80F degrees, in as soon as 15-30 minutes.

Clean Up/Release Removal

Clean the surface using a mild degreaser, mild dish soap or TSP, to remove all of the release previously applied. A floor scrubber or power washer will help to loosen and remove the film.

Limitations

- This product is designed for professional use only.
- Do not apply in temperatures below 55°F or above 80°F. Hot or cold weather may effect dry times.
- Test compatibility with Stamping Mats prior to using.
- Do not apply over an area of more than ten to fifteen square feet at a time, as the Stamp Release may evaporate before the stamp mats are placed over it.
- When stamping is complete, wash off the Stamp Release from the stamping mats using soap and water.
- Do not thin product.
- Do not allow Westcoat products to freeze.

Health Precautions

Inhalation of vapor or mist can cause headache, nausea, irritation of nose, throat and lungs. Prolonged or repeated skin contact can cause slight skin irritation.

Solvent based products are extremely flammable, extinguish all pilot lights and sources of ignition such as electrical motors. Be sure to have adequate cross ventilation prior to installing.

DISCLAIMER: PURCHASER'S SOLE AND EXCLUSIVE REMEDY AGAINST THE MANUFACTURER OF WESTCOAT, SHALL BE LIMITED SOLELY TO THE REPLACEMENT OF ANY DEFECTIVE MATERIAL OR A PAYMENT BY THE MANUFACTURER IN AN AMOUNT EQUAL TO THE COST OF THE ORIGINAL MATERIAL.



westcoat[®]

4007 Lockridge St • San Diego, CA 92102
800-250-4519 • Fax 619-255-7187 • westcoat.com

2 of 2
CA-20 12/19