



## Temper-Crete™ RT/RTB Systems – Self-Educated Training

Welcome to Westcoat's Temper-Crete™ RT/RTB Self-Educated Training. The purpose of this course is to increase your knowledge of our Temper-Crete™ RT and RTB systems.

This is a two-step process that will take approximately 45 minutes to complete. You will be required to complete a short test and submit your answers.

### Education

1. Spec Sheets: The **Temper-Crete™ RT** and **Temper-Crete™ RTB** system spec sheets contain detailed information on uses, materials, and coverage rates for these systems. The specs also have detailed instructions on the proper application steps from preparation to final coat to achieve a successful installation.
2. Materials Cost: Westcoat's Materials Cost Template is a powerful tool for you and your customers. Click below, find and download the Material Cost Template, then estimate the materials and associated cost a 500 sq ft job.

Temper-Crete System Page → scroll down to find the **Material Cost Template**

\*Alternatively, the **Material Estimator** shows the material needed without pricing.

3. Color Chart: The Temper-Crete™ system is available in a variety of colors and finishes, click to review the color charts:

**Temper-Crete™**

**Topcoats**

4. Tools: Get familiar with the recommended tools needed to install this system.

### Temper-Crete Tool Guide

Now to test all the valuable knowledge you've learned, continue to the next page.

## TEST

1. What type of material is Temper-Crete™?
  1. Concrete
  2. Mortar
  3. Epoxy
  4. Polyurethane
2. What is a Temper-Crete™ advantage? Check all that apply.

|   |  |
|---|--|
| <input type="checkbox"/> Pretty         | <input type="checkbox"/> Fast Turnaround |
| <input type="checkbox"/> Heat Resistant | <input type="checkbox"/> Heavy Duty      |
3. Where are ideal spaces for this system to be installed?

|   |
|---|
| <input type="checkbox"/> Balconies, Basements, Fountains                    |
| <input type="checkbox"/> Restaurants, Warehouses, Pharmaceutical Facilities |
4. What are the Westcoat materials that make up the Temper-Crete™ RT system?

|   |
|---|
| <input type="checkbox"/> EC-24 Urethane, TC-75 Cement                 |
| <input type="checkbox"/> EC-72 Patch Gel, EC-12 Primer, EC-34 Topcoat |
5. What components are added into the Broadcast version of this system?

|   |
|---|
| <input type="checkbox"/> SC-35 WB Stain, SC-65 Polyurethane Topcoat |
| <input type="checkbox"/> TC-65 Quartz Sand, EC-102 Polyaspartic     |
6. True or False: Primer is a mandatory step for the Temper-Crete™ coat.

|  |
|--|
| <input type="checkbox"/> True, primer is a required step.                  |
| <input type="checkbox"/> False, primer is an optional step in this system. |
7. What is Temper-Crete™ RT's coverage at ¼ inch per batch?

|                                    |
|------------------------------------|
| <input type="checkbox"/> 43-46 ft² |
| <input type="checkbox"/> 28-31 ft² |
8. How long does the material need to be mixed before application?

|   |
|---|
| <input type="checkbox"/> 2-3 minutes        |
| <input type="checkbox"/> approx. 60 seconds |
9. What is the dry time for these systems?

|   |
|---|
| <input type="checkbox"/> Light foot traffic 8 hours and heavy traffic 24 hours  |
| <input type="checkbox"/> Light foot traffic 18 hours and heavy traffic 72 hours |
10. What are the finishing options for these systems?

|   |
|---|
| <input type="checkbox"/> Applying Liquid Dazzle or Texture-Crete™ over the top.       |
| <input type="checkbox"/> Broadcasting chips or quartz sand and a variety of topcoats. |

**Name:**

**Branch name/Location:**