



Self-Educated Training – Shur Deck/Pro

Welcome to Westcoat's Self-Educated Training. The purpose of this course is to increase your knowledge of the Shur Deck and Shur Deck Pro systems.

This is a two-step process that will take approximately 30 minutes to complete. You will be required to complete a short test and submit your answers.

Education

1. System: Review the **Shur Deck System Page** on our website.



2. Spec Sheet: The spec sheets contain detailed information on the **uses, materials, coverage rates**, etc for this system. The specs also have detailed instructions on the proper application steps from preparation to final coat to achieve a successful installation. Click below to read the spec sheets:

Shur Deck

Shur Deck Pro

3. Materials and Cost: These are powerful tools for you and your customers. There are two tools for estimating the amount for product and the cost of product.

- From the system page > scroll down to find the **Material Cost Template** tab, click to download the Excel file. Open, plug in your pricing and the square footage to estimate the materials and associated cost a 500 sq ft job.
- Alternatively, the **Material Estimator** shows the amount of material needed without pricing.

*Alternatively, the **Material Estimator** shows the material needed without pricing.

3. Color Chart: The Shur Deck systems are available in a variety of standard colors. Click to review the color charts:

Topcoat Color Chart

4. Tools: Get familiar with the recommended tools needed to install this system.

Shur Deck Tool Guide

Now that you have read through the system resources you can test what you've learned. This can be printed but has been created to complete on your computer. Continue to the next page.

Shur Deck/Pro Quiz

Name:

Dist/Branch:

1. Where can the Shur Deck and Shur Deck Pro Systems be applied?
A. Only on interior concrete floors
B. Exterior walking decks, balconies, and breezeways
C. On vertical walls and ceilings
D. Below-grade basements
2. What is the minimum acceptable plywood thickness for installation?
A. 1/2 inch
B. 5/8 inch (3/4 inch preferred)
C. 1 inch
D. 7/16 inch
3. What is the minimum finished thickness of either system?
A. 1/8 inch
B. 3/8 inch
C. 1/4 inch
D. 1 inch
4. Which two ASTM tests verify the system's fire ratings?
A. ASTM D4060 and ASTM D4541
B. ASTM E-108 and ASTM E-119
C. ASTM C109 and ASTM D570
D. ASTM C794 and ASTM D638
5. Which lath option provides maximum protection against corrosion?
A. WP-25 Metal Lath
B. WP-35 Aluminum Lath
C. WP-30 Westcoat Glass Lath
D. WP-40 Sheet Membrane
6. What is the approximate Base Coat coverage when using WP-30 Glass Lath?
A. 60–70 sq ft per mix
B. 45–50 sq ft per mix
C. 30 sq ft per mix
D. 15 sq ft per mix
7. What major difference sets Shur Deck Pro apart from the standard Shur Deck?
A. It includes a reinforced waterproofing membrane layer
B. It is designed for interior use only
C. It eliminates the topcoat layer
D. It uses a thinner cement base
8. For Shur Deck Pro, what are the WP-95 Waterproofing Membrane coverage rates on the deck?
A. 80 sq ft first coat / 200 sq ft second coat
B. 60–65 sq ft first coat / 140–150 sq ft second coat
C. 45 sq ft first coat / 90 sq ft second coat
D. 100 sq ft first coat / 300 sq ft second coat
9. How long should the Body Coat dry before applying the second coat?
A. 30 minutes
B. 1 hour
C. 2 hours minimum
D. 6 hours minimum
10. How often should the Shur Deck Pro System be inspected and resealed?
A. Inspect every 6–8 years, reseal every 10 years
B. Inspect every 2–4 years, reseal every 3–5 years
C. Inspect every 1 year, reseal every 2 years
D. Inspect every 5 years, reseal every 7 years