



## KEYNOTES

- ① Exterior Grade Plywood
- ② WP-40 Sheet Membrane
- ③ WP-35 ALX Drain (By Westcoat)
- ④ WP-25 Metal or WP-30 Glass Lath
- ⑤ Base Coat
- ⑥ WP-95 Membrane & Fabric (PRO)
- ⑦ Body Coat
- ⑧ Texture Coat (Optional)
- ⑨ SC-10 Acrylic Topcoat

### IAPMO ER - 517

- Standard overlap is bottom to top with a 4" overlap.
- For maximum adhesion, WP-43 Sheet Membrane Primer should be used.
- Apply WP-53 on all flashing seams and overlaps.
- Minimum 5/8" exterior grade plywood.
- Minimum 1/4" slope required on all decks.
- Refer to local building codes and standards.
- Refer to system and product specification sheets.

All details are for reference only and should be evaluated by architect. These details are not a substitute for specifications, plans or evaluation reports. Architect, consultant or similar professional should be review prior to major waterproofing applications.

REV. 8/14/25 TC

## SHUR DECK PRO SYSTEM - DRAIN DETAIL

DIVISION 07 18 13  
Pedestrian Traffic Coatings

SCALE : NTS



**westcoat**  
SPECIALTY COATING SYSTEMS

4007 Lockridge Street • San Diego, CA • 92102  
800.250.4519 • westcoat.com