

KEYNOTES

- (3/4" Recommended)
- (2) WP-40 Sheet Membrane (6" or 36")
- (3) 26 Gauge, Bonderized Flashing
- (4) WP-25 Metal or WP-30 Glass Lath
- (5) Base Coat
- (6) WP-95 Membrane & Fabric (Pro System)
- (7) Body Coat
- 8 Texture Coat (Optional)
- Topcoat
- (10) Building Paper (By Others)
- (11) Stucco Finish (By Others)

IAPMO ER - 517

- Standard overlap is bottom to top with a 4" overlap.
- For maximum adhesion, WP-43 Sheet Membrane Primer should be used.
- \bullet Apply WP-53 on all flashing seams and overlaps.
- Minimum 5/8" exterior grade plywood.
- · Minimum 1/4" slope required on all decks
- · Refer to local building codes and standards.
- Refer to system and product specification sheets.

All details are for reference only and should be evaluated by architect. These details are not a substitute for specifications, plans or evaluation reports. Architect, consultant or similar professional should be review prior to major waterproofing applications.

SHUR DECK SYSTEM - EDGE METAL FLASHING OVER STUCCO FASCIA

DIVISION 07 18 13 Pedestrian Traffic Coatings

SCALE: NTS



westcoat.

SPECIALTY COATING SYSTEMS

4007 Lockridge Street • San Diego, CA • 92102 800.250.4519 • westcoat.com