


KEYNOTES	
① 5/8" MIN. Exposure 1 Sheathing (3/4" Recommended) ② WP-40 Sheet Membrane (6" or 36") ③ 26 Gauge, Bonderized Flashing ④ WP-25 Metal or WP-30 Glass Lath ⑤ Base Coat ⑥ WP-95 Membrane & Fabric (Pro System) ⑦ Body Coat ⑧ Texture Coat (Optional) ⑨ SC-10 Topcoat ⑩ Building Paper (By Others) ⑪ Stucco Finish (By Others)	
IAPMO ER - 517	
<ul style="list-style-type: none"> • Standard overlap is bottom to top with a 4" overlap. • For maximum adhesion, WP-43 Sheet Membrane Primer should be used. • Apply WP-53 on all flashing seams and overlaps. • Minimum 5/8" exterior grade plywood. • Minimum 1/4" slope required on all decks. • Refer to local building codes and standards. • Refer to system and product specification sheets. 	
<small>All details are for reference only and should be evaluated by architect. These details are not a substitute for specifications, plans or evaluation reports. Architect, consultant or similar professional should be review prior to major waterproofing applications.</small>	
<div> <div>SHUR DECK SYSTEM - EDGE METAL TO GUTTER</div> <div> <div>DIVISION 07 18 13 Pedestrian Traffic Coatings</div> <div>SCALE : NTS</div> </div> </div> <div>  <div> westcoat SPECIALTY COATING SYSTEMS 4007 Lockridge Street • San Diego, CA • 92102 800.250.4519 • westcoat.com </div> </div>	

REV. 8/14/25 TC