



KEYNOTES

- ① WP-40 Sheet Membrane
- ② WP-25 Metal or WP-30 Glass Lath
- ③ Base Coat
- ④ WP-95 Membrane & Fabric (PRO SYSTEM)
- ⑤ Body Coat
- ⑥ Texture Coat (Optional)
- ⑦ SC-10 Topcoat
- ⑧ 26 Gauge, Bonderized Flashing
MIN. 4" on deck and 6" height. Overlap wall to deck flashing 4" on either side of opening.
- ⑨ Threshold Flashing Pan
- ⑩ WP-53 Hybrid Sealant Between flashing and threshold, as well as between door jamb and threshold
- ⑪ Full embedment of WP-53 between flashing and compress together
- ⑫ WP-53 Sealant

IAPMO ER - 517

- Standard overlap is bottom to top with a 4" overlap.
- For maximum adhesion, WP-43 Sheet Membrane Primer should be used.
- Apply WP-53 on all flashing seams and overlaps.
- Minimum 5/8" exterior grade plywood.
- Minimum 1/4" slope required on all decks.
- Refer to local building codes and standards.
- Refer to system and product specification sheets.

All details are for reference only and should be evaluated by architect. These details are not a substitute for specifications, plans or evaluation reports. Architect, consultant or similar professional should be review prior to major waterproofing applications.

REV. 8/20/25 TC

SHUR DECK SYSTEM - TWO PIECE DOOR PAN FLASHING

DIVISION 07 18 13
Pedestrian Traffic Coatings

SCALE : NTS



westcoat
SPECIALTY COATING SYSTEMS

4007 Lockridge Street • San Diego, CA • 92102
800.250.4519 • westcoat.com